

SecoFlex exterior masonry paint

Stops rain penetration
Saves energy
Improves flood resistance

Wall Coating that protect building walls for many, many years!

If you are suffering with a cold house, rising damp or penetrating damp then our exterior wall solutions can help.

We can guarantee when our coloured solution is applied to your exterior walls it will waterproof your building and make your home more energy efficient.

Damp walls are thermal bridges – If moisture collects in the pores of your brickwork, more heat is transferred than would be possible if they were waterproofed and filled with air. Our products eliminate this, ensuring you a more energy efficient home.

Our products have been independently tested to confirm these exceptional characteristics, so you can be rest assured – that by having a SecoFLEX installation on your property, you're giving your home the best, long lasting and energy efficient protection currently available on the market today.

Stops rain penetration

Saves energy

Improves flood resistance



Tried and tested quality

For waterproofing any wall

An elastic, crack bridging and waterproofing masonry coating. The microporous structure ensures that your building is constantly able to breathe. In other words, **wall protection with waterproof guarantees.**

- **100% Waterproof:** a building treated with SecoFLEX Waterproofing Coating is guaranteed to remain bone-dry.
- **400% Elastic:** the permanent elasticity protects your building optimally in all circumstances and prevents tears, flaking and blistering.
- **Permeable to water vapour:** your building can breathe at all times with SecoFLEX.
- **Crack bridging**
- **Resistant to contamination and ageing** in all weather conditions and climates.
- **Water based**
- **Colourfast:** the unique SecoFLEX formula means that even deep and dark colours are not affected by sunlight.
- **Protects reinforced concrete** against carbonation, penetration of chlorides, corrosion and damaging salts.
- **Improves thermal resistance** of brickwork and masonry by keeping it dry.

The high elasticity and waterproofing of SecoFLEX coating save your walls from ageing, damage and penetrating damp

TECHNICAL REFERENCE

Water based

Coverage: Apply in 2 coats @300-600g/m²/ coat

Dry to touch: 45min

Dry to recoat: 24hrs

Substrates: Existing sound paintwork can be coated directly with SecoFLEX



Prolong the lifetime of your building

Example defects cured by the WeatherGuard coating system:



ALGAE GROWTH



BLISTERING



SPALLING



CRACKING



AIRBOURNE POLLUTION



EFFLORESCENCE

With the correct level of preparation all these commonly seen problems can be cured with a WeatherGuard installation. If you are suffering with any of these issues then why not get in touch so that we can assist you in addressing these problems.

Colours

Our coloured masonry protection paint is available in 12 standard colours.



WeatherGuard Home Solutions Ltd
557 Valley Road, Nottingham, NG5 1JE
+44 (0)800 677 1050

info@weatherguardhome.co.uk
www.weatherguardhome.co.uk

